

energy HT1600 Overlap welding kit



To the product



Technical data

Voltage	120 V; 220 V; 230 V	
Frequency	50/60 Hz; 60 Hz	
Power	1600 W	
Temperature	40-700 °C	104.0-1292.0 °F
Temperature setting stepless	Yes	
Airflow (20°C)	240 l/min	8.47 cfm
Stepless air volume adjustment	No	
Static pressure	2600 Pa	0.37 psi
Eco-Mode	No	
Display	No	
e-Drive	No	
Outdoor use	Yes	
Nozzle connection ø	31.5 mm / 1.25 in	
Length	346.0 mm	13.62 in
Device diameter	101 mm	3.97 in
Handle diameter	59 mm	2.32 in
Weight	0.99 kg	2.18 lb
Power cable length	3.0 m	9.84 ft
Noise emission level	67 dB (A)	

energy HT1600 Overlap welding kit

Technical data

Approvals	CE; KC
Protection class	II
Country of origin	CN

Scope of delivery

Pressure roller 40 mm, silicone; Carbon brushes; Wide slot nozzle (ø 31.5) 40 x 2 mm; Wide slot nozzle (ø 31.5) 20 x 2 mm

Product items

120.882	energy HT1600, 230V/1600W, overlap kit, EU plug
120.885	energy HT1600, 120V/1600W, overlap kit, US plug
120.888	energy HT1600, 230V/1600W, overlap kit, CN plug
126.767	energy HT1600, 230V/1600W, overlap kit, UK plug
127.016	energy HT1600, 220V/1600W, overlap kit, KR plug
166.210	energy HT1600, 230V/1600W, overlap kit, AU plug